



Stereo 60 MKIII

Upgraded Circuit
New KT150 Design
With 6SN7s & 6SL7s
80+80 watts RMS*
50+50w Triode Mode
Choke Power Supply
Remote Control
Tape Monitor

New Features:
Tertiary Transformers
Valve Regulator
Improved Finish
Plexiglas Valve Cover
Standby Circuit

designed by David Shaw

*Low Distortion Tertiary
wound transformers*

Now in matt finish. Shown with optional David Shaw CV181s and FM TJ 6SL7s

The Worlds First KT150 Integrated UL/Triode Hi Fi Amplifier

An OUTSTANDING Integrated Amp!

This is our most powerful integrated amplifier. It is ideal for someone wanting a very dynamic fast sound. It has a big power supply, big output transformers, and designed for the excellent new Tung-sol KT150/120. And it comes with many features!

An integrated version of our MB90 MKIIs. The original design got the best out of the KT88, now re-designed for the KT150 which we believe has even better sonics.

The MK III design comes with our new "LDT" low distortion transformers, a valve regulated first stage, and a copper alloy top plate.

Integrated & Power Amplifier in One!

A special feature is the ability to change the sensitivity of Stereo 60 MKIII at the flick of a switch. Choose between use as either an integrated remote control amplifier, or as a power amplifier fed from a separate pre-amplifier.

Triode and Ultralinear Amplifier in One

The triode sound is preferred by many hi fi fans, but the power is always lower. With our UL/Triode switch you can change from 80 watts to 50 watts of pure triode sound by changing the switch.

Specifications and Features

- May be used as a power amplifier
- Comprehensive manual supplied
- Built in bias & valve test meter
- Hand wired point to point
- Japanese Blue ALPS volume pot.
- Class A, Triode front end
- Output circuit Ultralinear or Triode switchable
- 4x KT150 or KT120
- KT88/6550 compatible*
- 2x 6SL7 first stage valves
- 2x 6SN7 output driver valves
- 2x 80 Watts Ultralinear
- 2x 50 Watts Triode mode
- Signal to noise level -90db
- Frequency response 20hz-20kHz +0 – 0.5db full power
- THD less than 0.05% 1khz
- 4 and 8 ohm loudspeaker outputs
- LDT Tertiary Custom hand wound output transformers
- Attractive cover included in the price
- Solen Hi Fi quality audio capacitors
- Mundorf capacitor upgrade on request
- Silver PTFE audio cable
- Gold plated Input & speaker terminals
- Four line inputs
- Tape monitor circuit
- 350mv input sensitivity.(high) 1.2v (low)
- 220/240volts 200watts typ, 500w max
- C E. ROHS.
- 43cmW, 38D, 23H, 35kg

*Can be de-rated for KT88/6550
(Specifications subject to change)

**HI FI WORLD TEST
VERDICT**

