

# NEW Stereo 60 MK IV

New Upgraded Circuit  
Designed for KT150/170  
Uses Superb 6SN7  
85+85 Watts UL  
50+50 Watts Triode  
Choke Power Supply  
Remote Control  
Record Loop



*designed by David Shaw*

*Low Distortion Tertiary  
wound transformers*

Shown with David Shaw 6SN7/CV181

## An Updated MK IV version of our powerful KT150 Integrated Hi Fi Amplifier

### An OUTSTANDING Amplifier!

This is our most powerful integrated amplifier. It is ideal for someone wanting a very dynamic fast sound. It has a big power supply, big output transformers, and a big sound. Designed to get the best from the excellent new Tung-sol KT150/120. And it comes with many features!

Based on our MB90 monoblock power amplifiers the Stereo 60 offers the convenience of one unit not requiring a separate pre-amplifier.

The original design got the best out of the KT88, now re-designed for the KT150 which we believe has even better sonics.

The MK IV design comes with our new "LDT" low distortion transformers, and a redesigned front end.

The ST60 MK IV is similar to the MK III version but with a re-designed front end using four 6SN7s which means that only two types of valves are used. This enhances the performance with lower distortion and better macro dynamics.

### Integrated & Power Amplifier in One!

A special feature is the ability to change the sensitivity of Stereo 60 MKIV at the flick of a switch. Choose between use as either an integrated remote control amplifier, or as a power amplifier fed from a separate pre-amplifier.

### Triode and Ultralinear Amplifier in One

The triode sound is preferred by many hi fi fans, but the power is always lower. With our UL/Triode switch you can change from 85 watts to 50 watts of pure triode sound by changing the switch.

### Specifications and Features

- May be used as a power amplifier
- Comprehensive manual supplied
- Built in bias & valve test meter
- Hand wired point to point
- Japanese Blue ALPS volume pot.
- Class A, Triode front end
- Output circuit Ultralinear or Triode switchable
- 4x KT150/170 or KT120
- KT88/6550 compatible\*
- 4x 6SN7 output driver valves (CV181)
- 2x 85 Watts Ultralinear
- 2x 50 Watts Triode mode
- Signal to noise level -90db
- Frequency response 20hz-20kHz +0 – 0.5db full power
- THD less than 0.05% 1khz
- 4 and 8 ohm loudspeaker outputs
- LDT Tertiary Custom hand wound output transformers
- Attractive cover included in the price
- Solen Hi Fi quality audio capacitors
- Capacitor upgrade option
- Silver plated PTFE audio cable
- Gold plated Input & speaker terminals
- Four line inputs
- Tape monitor circuit
- 350mv input sensitivity.(high) 1.2v (low)
- 220/240volts 200watts typ, 500w max
- C E. ROHS.
- 43cmW, 38D, 23H, 35kg

\*Can be de-rated for KT88/6550

(Provisional specifications subject to change)

### Summary:

**A powerful Push-Pull integrated or power amplifier with of exceptional performance driving demanding speakers. Also Offering 50W of Pure Triode Power at an affordable price!**